

N.T.A. AIRBRAKE FITTINGS

NTA AIRBRAKE FITTINGS: are manufactured specifically for use in truck trailer air braking systems. There are easy to assemble fittings can also be used in secondary air systems where D.O.T approved fittings are required. NTA Airbrake Fittings are available in 1/4" to 1/2" Pipe Threads and 1/4" to 5/8" tubing sizes.

ADVANTAGES: Easy to assemble with no tube preparation or bending required. NTA Airbrake Fittings have a built in tube support and can be assembled and disassembled many times.

APPLICATIONS: These fittings are designed specifically for use in Truck and Trailer air braking systems expect where temperature exceeds 200 degrees fahrenheit or where battery acid can drip to the tubing.

WORKING PRESSURE: Up to 150 P.S.I.

FITTING SPECIFICATIONS: NTA Airbrake Fittings are manufactured to meet D.O.T. FMVSS 571.106 airbrake specifications.

TUBING SPECIFICATIONS: NTA Airbrake Fittings meet the functional requirements of the SAE automotive fitting standards: SAE J246 and SAE J1131. Use with SAE Type A and B Nylon Airbrake Tubing.



Patlin has made a concerted effort to provide accurate information, however Patlin assumes no responsibility for the accuracy of the information.

Printed in U.S.A.

Connect with us on:



855.728.5460 www.patlininc.com

