

RTV SILICONE GASKET MARKER BLACK

This R.T.V. Sealant Adhesive can be used on metal, glass, porcelain, ceramics, wood, rubber, and most paint and plastics. As an instant gasket maker, this product replaces a wide range of cork, paper, asbestos, felt and metal gaskets. This product has excellent adhesion characteristics, high chemical resistance and will not sag or shrink. Withstands intermittent temperatures up to 600°F and pressures up to 330 psi. Offers unmatched performance under the most severe operating conditions. Virtually unaffected by chemical deterioration, extreme weather, temperature or aging.



Features:

M12011

BLACK

RTV SILICONE

RTV Masilla Sellante de Silicona

Low Volatile = Flexible = Easy to Use Baja Volatilidad • Flexible • Fácil de Usar Remains permanently flexible at temperatures from -60°F to +500°F remanece flexible permanentemente a temperaturas de -60 °C a + 500 °F Safe to use on oxygen sensor equipped vehicles Seguro de usar en vehiculos equipados con sensor de oxigeno Waterproof = Weatherproof A preba de Aua • Besistente a la Intemperie

CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. CONTENTS UNDER PRESSURE

OUTER CONTAINER

HER CAUTIONS ON

UNDER PRESSURE. Essurized with a flammable Carbon Propellant. Plug in Bottom of Container Back Panel. Keep out of reac

NEDOR, DE GUMA EN LA PARTE INFERIOR DEL NEDOR, VER OTRAS PRECAUCIONES EN EL PAÑEL OR MANTENER FUERA DEL ALCANCE DE LOS NINOS NET WT. / PESO NETO: 8 02 / 227 g

- Seals, Bonds, Insulates Low Volatile Flexible
- Easy to Use Economical Eliminates Waste
- Waterproof Weatherproof
- Eliminates: Squeeze Tubes & Cartridge Guns
- 100% Low Volatile R.T.V. Silicone
- Meets G.M. and O.E.M. specifications
- Safe to use on oxygen sensor equipped vehicles



For use on:

Pumps, High Pressure Pipe Joints, Oil and Transmission Pans, Oil and Water Pumps, Valve and Timing Chain Covers, Electric Motors and Electrical Control Boxes, Gear Boxes, Compressors, Machine Covers, Rigid Flange Assemblies, Equipment Housings

Characteristics:	
Temperature Range	Cures at room temperature, range from -60°F to +500°F
Waterproof	Yes
Appearance	Black Paste
Shipping Weight	12 Pounds

Patlin Part #

M12011







Printed in U.S.A.

855.728.5460 📑 www.patlininc.com