



This R.T.V. Sealant Adhesive can be used on metal, glass, porcelain, ceramics, wood, rubber, and most paint and plastics. As an instant gasket maker, this product replaces a wide range of cork, paper, asbestos, felt and metal gaskets. This product has excellent adhesion characteristics, high chemical resistance and will not sag or shrink Withstands intermittent temperatures up to 650°F and pressures up to 330 psi. Offers unmatched performance under the most severe operating conditions. Virtually unaffected by chemical deterioration, extreme weather, temperature or aging.



Features:

M12021

RED HI-TEMP

V SILICO

RTV Masilla Sellante de Silicona

Seals, Bonds, Insulates Sella, Une, Aisla

Low Volatile = Flexible = Easy to Use Baia Volatilidad • Flexible • Fácil de Usar

Remains permanently flexible at temperatures from -60°F to +650°F ce flexible permanente

CONTENTS UNDER PRESSURE OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROFLUOROCARBON PROPELLANT.

EDOR. VER OTRAS PRECAUCIONES EN EL PARTE AMANTENER FUERA DEL ALCANCE DE LOS NINO ET WT. / DESO NIETO, O OTRAS DE LOS NINO NET WT. / PESO NETO: 8 OZ / 227 g

turas de -60 °F + 650 °F Waterproof • Weatherproof A Prueba de Aqua • Resistente a la Intemperie

nente a

INT CAUSES IRRITATION.

ION PROPELLANT. In Bottom of Contained Panel, keep out of read

SELLADOR SIN CURA INTENIDO BAJO PRES Esta presurizado (

RT

- Seals, Bonds, Insulates Low Volatile Flexible
- Easy to Use Economical Eliminates Waste
- Waterproof Weatherproof
- Eliminates: Squeeze Tubes & Cartridge Guns
- 100% Low Volatile R.T.V. Silicone
- Meets G.M. and O.E.M. specifications
- Safe to use on oxygen sensor equipped vehicles



For use on:

Pumps, High Pressure Pipe Joints, Oil and Transmission Pans, Oil and Water Pumps, Valve and Timing Chain Covers, Electric Motors and Electrical Control Boxes, Gear Boxes, Compressors, Machine Covers, Rigid Flange Assemblies, Equipment Housings

| Characteristics: | |
|-------------------|---|
| Temperature Range | Cures at room temperature, range from -60°F to +650°F |
| Waterproof | Yes |
| Appearance | Red Paste |
| Shipping Weight | 12 Pounds |

Patlin Part #

M12021



855.728.5460 www.patlininc.com

Connect with us on:

